

# imageRUNNER ADVANCE C7500 III series

# EXCELLENT COLOUR QUALITY COMMUNICATION




Canon uniFLOW Online  
Outstanding Cloud Output Management Solution



Canon imageRUNNER ADVANCE C7580i  
Outstanding 70- to 80-ppm Colour Copier MFP




## MAIN CONFIGURATION OPTIONS




**STAPLE FINISHER-V2**

- 3 tray, 3,500 sheet capacity
- Corner and double stapling up to 65 sheets (90 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple on Demand 65 sheets (90 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers (2/4 Hole Puncher Unit-A1 and 4 Hole puncher unit-A1)




**DOCUMENT INSERTION UNIT-G1**

- Insert pre-printed sheets
- Up to A3
- 1-tray, 100 sheet capacity




**DOCUMENT INSERTION/ FOLDING UNIT-K1**

- Insert pre-printed sheets
- Up to A3
- 1-tray, 100-sheet capacity
- Z-fold and C-fold




**STAPLE FINISHER-X1**

- 3 tray, 4,250 sheet capacity
- Corner and double stapling up to 100 sheets (80 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers (Puncher Unit-BG1 (2/F4H) and Puncher Unit-BH1 (S4H))




**DOCUMENT INSERTION UNIT-N1**

- Insert pre-printed sheets
- Up to A3
- 2-tray, 400 sheet capacity




**PAPER FOLDING UNIT-J1**

- Insert pre-printed sheets
- Up to A3
- Z-fold, Accordion Z-Fold, C-fold, Half-Fold and Double Parallel Fold




**MULTI FUNCTION PROFESSIONAL PUNCHER-A1**

- Up to A3
- Media weight 52 - 300 gsm




**PAPER DECK UNIT-E1**

- Supports A4
- Media weight 52 - 256 gsm
- 3,500 sheets (80gsm)




**POD DECK LITE-C1**

- Supports up to A3
- Media weight 52 - 300 gsm
- 3,500 sheets (80 gsm)



**MULTI DRAWER PAPER DECK-C1**


- Supports up to A3
- Media weight 52 - 300 gsm
- 6,000 sheets (80 gsm)



**IMAGEPASS-N2**

<b>PDL</b>	• PCL/PS
<b>MEMORY</b>	• 4GB/500GB
<b>SYSTEM</b>	• Fiery FS350

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalised printing with the built-in, entry-level Fiery FreeForm (TM) or with the supported industry-leading variable data printing (VDP) formats
- Integrates print production workflows with EFI (TM) management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules



**IR-ADV C7565i III\*/  
IR-ADV C7570i III\*/  
IR-ADV C7580i III\***

This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the online product configurator.

III\* indicates that this model has been upgraded to new system software and includes additional security features as standard.

# TECHNICAL SPECIFICATIONS

# imageRUNNER ADVANCE C7500 III series

## MAIN UNIT

**Machine type**  
**Core functions**  
**Processor**  
**Control Panel**

A3 Colour Laser Multifunctional  
 Print, Copy, Scan, Send, Store and Optional Fax  
 Canon Dual Custom Processor (Shared)  
 Standard: 25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touch panel  
 Optional: 26.4 cm (10.4 inch) TFT LCD SVGA Colour Upright Touch Panel  
 Standard: 4.0GB RAM  
 Standard: 250GB, Maximum: 1TB  
 Optional: 250GB, 1TB  
 NETWORK  
 Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n);  
 Optional: NFC, Bluetooth Low Energy  
 OTHERS  
 Standard: USB 2.0 (Host) x2, USB 3.0 (Host) x1, USB 2.0 (Device) x1;  
 Optional: Serial Interface, Copy Control Interface

## Memory

**Hard Disk drive**  
**Mirroring Hard Disk Drive**  
**Interface Connection**

## Paper Supply Capacity (A4, 80gsm)

## Paper output capacity (A4, 80gsm)

## Finishing capabilities

Standard: 3,550 sheets 1,100-sheet Paper Deck x 2, 550-sheet Paper Cassette x 2, 250-sheet Multi-purpose tray  
 Maximum: 9,300 sheets (with MULTI-DRAWER PAPER DECK-C1)

250 Sheets (with COPY TRAY-R2)  
 Maximum: 4,250 Sheets (with STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)

Standard: Collate, Group  
 With External Finisher : Collate, Group, Offset, Staple, Saddle Stitch<sup>\*1</sup>, Hole Punch<sup>\*2</sup> (multiple patterns), Staple-Free Staple<sup>\*3</sup>, Staple on Demand<sup>\*3</sup>, Document Insertion<sup>\*4</sup>, Fold (C<sup>\*5</sup>, Z<sup>\*5</sup>, Half<sup>\*6</sup>, Double parallel<sup>\*6</sup>, Accordion-Z fold<sup>\*6</sup>), Trimming<sup>\*7</sup>  
<sup>\*1</sup> Requires Booklet Finisher-V2 or Booklet Finisher-X1  
<sup>\*2</sup> Requires 2/4 Hole Puncher Unit-A1 or 4 Hole Puncher Unit-A1 (with Staple Finisher-V2 or Booklet Finisher-V2) or Puncher Unit-BG1 or Puncher Unit-BH1 or Multi Function Professional Puncher-A1/B1 (with Staple Finisher-X1 or Booklet Finisher-X1)  
<sup>\*3</sup> Requires Staple Finisher-V2 or Booklet Finisher-V2  
<sup>\*4</sup> Requires Document Insertion Unit-Q1 or Document Insertion/Folding Unit-K1 (with Staple Finisher-V2 or Booklet Finisher-V2) or Document Insertion Unit-N1 (with Staple Finisher-X1 or Booklet Finisher-X1)  
<sup>\*5</sup> Requires Document Insertion/Folding Unit-K1 (with Staple Finisher-V2 or Booklet Finisher-V2) or Paper Folding Unit-J1 (with Staple Finisher-X1 or Booklet Finisher-X1)  
<sup>\*6</sup> Requires Paper Folding Unit-J1 (with Staple Finisher-X1 or Booklet Finisher-X1)  
<sup>\*7</sup> Requires Inner Booklet Trimmer-A1 (with Booklet Finisher-X1)

## Supported media types

Paper Decks (1/2): Thin, Plain, Recycled, Thick, Colour, Transparency, Pre-punched, Letterhead, Bond  
 Paper Cassettes (3/4): Thin, Plain, Recycled, Thick, Colour, Tab\*, Transparency, Bond, Pre-punched, Letterhead, Envelope  
<sup>\*Requires Tab Feeding Attachment-F1</sup>

Multi-purpose tray: Thin, Plain, Recycled, Thick, Colour, Transparency, Label, Tracing\*, Envelope, Coated, Textured, Bond, Pre-punched, Letterhead, Tab  
<sup>\* Some types of tracing paper cannot be used.</sup>

## Supported media sizes

Paper Decks (1/2):  
 Standard size: A4, B5  
 Paper Cassettes (3/4):  
 Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R (Simplex only), B4, B5, B5R,  
 Envelope [No.10 (COM10), Monarch, ISO-C5, DL]  
 Envelope custom size: 98.0 x 148 mm to 330.2 x 487.7 mm  
 Custom Size: 139.7 x 182.0 mm to 330.2 x 487.7 mm  
 Multi-purpose tray:  
 SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Envelope [No.10 (COM10), Monarch, ISO-C5, DL]  
 Envelope custom size: 90.0 x 148 mm to 330.2 x 487.7 mm  
 Custom size: 100.0 x 148.0 mm to 330.2 x 487.7 mm  
 Free size: 100.0 x 182.0 mm to 330.2 x 487.7 mm

## Supported media weights

Paper Deck (1/2): 52 to 220 gsm  
 Paper Cassettes (3/4): 52 to 256 gsm  
 Multi-purpose tray: 52 to 300 gsm  
 Duplex: 52 to 220 gsm

From Power On: 30 Seconds or Less\*  
<sup>\* Time from device power-on, until copy ready (not print reservation)</sup>

## Warm-up Time

From Sleep Mode: 30 Seconds or Less  
 Quick Startup Mode: 4 seconds or less\*  
<sup>\*Time from device power-on to when key operations can be performed on the touch panel display.</sup>

## Dimensions (W x D x H)

## Installation Space(W x D)

689 x 941 x 1,220 mm  
 Basic-1: 1,758 x 1,524 mm (with Front door open + Multi-purpose tray/upper-right cover open + Left cover open)  
 Basic-2: 2,026 x 1,524 mm (with Front door open + Multi-purpose tray/upper-right cover open + Buffer Pass-M1 + Booklet Finisher-V2/extension tray & rotary tray extended )  
 Fully Configured: 3,818 x 1,524 mm (with Multi-Drawer Paper Deck-C1 + Buffer Pass-M1 + Document Insertion Unit-N1 + Multi Function Professional Puncher-A1 + Paper Folding Unit-J1 + Booklet Finisher-X1)  
 Approx. 269 kg (including toner)

## Weight

## PRINT SPECIFICATIONS

### Print Speed (BW/CL)

iR-ADV C7580i III: 80/70 ppm (A4, A5, A5R, A6R), 40/35 ppm (A3), 56/49 ppm (A4R)  
 iR-ADV C7570i III: 70/65 ppm (A4, A5, A5R, A6R), 35/32 ppm (A3), 49/46 ppm (A4R)  
 iR-ADV C7565i III: 65/60 ppm (A4, A5, A5R, A6R), 32/30 ppm (A3), 46/42 ppm (A4R)  
 Up to 2,400 x 2,400

### Print Resolution (dpi)

### Page description languages

### Direct Print

Standard: UFR II, PCL 6, Genuine Adobe PostScript Level 3  
 Direct printing available from USB memory, Advanced space, Remote UI and Web Access\*  
 Supported file types: TIFF, JPEG, PDF, EPS, and XPS  
<sup>\* Only PDF print from websites is supported</sup>

## Printing from mobile and cloud

AirPrint, Mopria, Google Cloud Print, and Canon PRINT Business, and uniFLOW Online

A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements.

Please contact your sales representative for further information  
 PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT J/K/S/T\*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts\*2  
 PS fonts: 136 Roman

<sup>\*1</sup> Requires optional PCL International Font Set-A1

<sup>\*2</sup> Requires optional Barcode Printing Kit-D1

## Fonts

## Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Front/Back Covers, Toner Reduction, Poster Printing, Forced Hold Printing

## Operating System

UFR II: Windows 7 / 8.1/10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016, MAC OS X (10.7 or later)  
 PCL: Windows 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016  
 PS: Windows 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016, MAC OS X (10.7 or later)  
 PPD: MAC OS X (10.7 or later), Windows 7 / 8.1/ 10

SAP Device Types are available via the SAP Market Place. Please refer to <http://www.canon-europe.com/support/business-product-support> for availability of print solutions for other operating systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable.

## COPY SPECIFICATIONS

### Copy Speed (BW/CL)

iR-ADV C7580i III: 80/70 ppm (A4, A5, A5R, A6R), 40/35 ppm (A3), 56/49 ppm (A4R)  
 iR-ADV C7570i III: 70/65 ppm (A4, A5, A5R, A6R), 35/32 ppm (A3), 49/46 ppm (A4R)  
 iR-ADV C7565i III: 65/60 ppm (A4, A5, A5R, A6R), 32/30 ppm (A3), 46/42 ppm (A4R)

### First-Copy-Out Time (A4) (BW/CL)

iR-ADV C7580i III: Approx. 4.4/5.4 seconds or less  
 iR-ADV C7570i III: Approx. 4.8/5.9 seconds or less  
 iR-ADV C7565i III: Approx. 4.8/5.9 seconds or less

### Copy resolution (dpi)

Reading: 600 x 600  
 Printing: Up to 2,400 x 2,400

### Multiple Copies

### Copy Density

### Magnification

### Preset Reductions

### Preset Enlargements

### Basic Copy Features

Up to 9,999 copies  
 Automatic or Manual (9 Levels)  
 25% - 400% (1% Increments)  
 25%, 50%, 70%  
 141%, 200%, 400%  
 Preset R/E Ratios by Area, Paper Setting, Previous Setting, Favourite Setting, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

## Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Detect Feeder Multi Sheet Feed, Free Size Original

## SCAN SPECIFICATIONS

### Type

Colour Platen and Single-pass Duplexing Automatic Document Feeder\* [2-sided to 2-sided (Automatic)]  
<sup>\* Detect Feeder Multi Sheet Feed is supported.</sup>  
 300 Sheets

### Document Feeder Paper Capacity (80 gsm)

### Acceptable originals and weights

Platen: Sheet, Book, 3-Dimensional Objects (Height: Up to 50 mm, Weight: up to 2kg)  
 Document Feeder media weight:

1-sided scanning: 38 to 220 gsm (BW), 64 to 220 gsm (CL)  
 2-sided scanning: 50 to 220 gsm (BW), 64 to 220 gsm (CL)

### Supported media sizes

Platen: max. scanning size: 297.0 x 431.8 mm  
 Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6R, Custom size: 128.0 x 139.7 mm to 304.8 x 431.8 mm

### Scan Speed (ipm: BW/CL; A4)

Single-sided Scanning: 120 /120 (300dpi), 120 /70 (600 dpi)  
 Double-sided Scanning: 240 /220 (300dpi), 150 /90 (600 dpi)

### Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

### Pull Scan Specifications

Colour Network ScanGear2. For both TWAIN and WIA  
 Supported OS: Windows 7/8.1/10  
 Windows Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

### Scan Method

Send functionality available on all models  
 Scan to USB Memory Key: Available on all models  
 Scan to Mobile Devices and cloud-based services: A range of solutions is available to provide scanning to mobile devices or cloud-based services depending on your requirements. Please contact your sales representative for further information.  
 TWAIN/WIA Pull scanning available on all models

## SEND SPECIFICATIONS

### Destination

E-mail/Internet FAX (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 FAX (Optional), IP Fax (Optional)

### Address Book

### Send resolution (dpi)

LDAP (2,000)/Local (1,600)/Speed dial (200)  
 600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

### Communication protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV  
 E-mail/Fax: SMTP, POP3



# TECHNICAL SPECIFICATIONS

# imageRUNNER ADVANCE C7500 III series

<b>File Format</b>	Standard: TIFF, JPEG, PDF (Limited Colour, Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b, Encrypted), XPS (Compact, Searchable), Office Open XML (PowerPoint, Word), PDF/XPS (Device Signature) Optional: PDF (Trace & Smooth), PDF/XPS (User Signature)	<b>CONSUMABLES</b> <b>Toner Cartridges</b> <b>Toner Yield (Estimated @ 5% Coverage)</b>	C-EXV 52 TONER BK/C/M/Y C-EXV 52 TONER BK: 82,000 pages C-EXV 52 TONER C/M/Y: 66,500 pages
<b>Universal Send Features</b>	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages, Detect Feeder Multi Sheet Feed	<b>SOFTWARE AND PRINTER MANAGEMENT</b> <b>Tracking and reporting</b>	Universal Login Manager* (ULM): Manage your costs easily by using the embedded reporting capability to identify and control costs on a user-based level by device.  uniFLOW Online Express: Combining with ULM you can gain further control and highlight expenditures per users/department and pinpoint where costs can be scaled down from a central cloud based location. *Installation, activation & registration required
<b>FAX SPECIFICATIONS</b> <b>Maximum Number of Connection Lines</b> <b>Modem Speed</b>	2  Super G3: 33.6 kbps G3: 14.4 kbps	<b>Remote management tools</b>	<b>iW Management Console:</b> Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management) <b>eMaintenance:</b> Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance) <b>Content Delivery System:</b> Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web based interface to each device that helps to provide remote device management and control <b>Network ScanGear:</b> TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device
<b>Compression Method</b> <b>Resolution (dpi)</b> <b>Sending/Recording Size</b>	MH, MR, MMR, JBIG 400 x 400, 200 x 400, 200 x 200, 200 x 100 A3, A4, A4R, A5*, A5R*, B4, B5*, B5R* *1 Sent as A4 *2 Sent as B4	<b>Scanning software</b>	
<b>FAX memory</b> <b>Speed dials</b> <b>Group dials/destinations</b> <b>Sequential broadcast</b> <b>Memory backup</b> <b>Fax Features</b>	Up to 30,000 pages Max. 200 Max. 199 dials Max. 256 addresses Yes Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density (for Scanning), Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed	<b>FIERY PRINT CONTROLLER SPECIFICATIONS (EMBEDDED)</b> <b>Optional/Standard</b> <b>Name</b> <b>Print Resolution (dpi)</b> <b>Page Description Language(s)</b> <b>Memory</b> <b>Hard Disk Drive</b> <b>Processor Speed</b> <b>System</b> <b>Fonts</b>	Optional on all models imagePASS N2 (Embedded) 1200 x 1200, 600 x 600 Adobe PS3, PCL6 4GB (1 x 4GB) 500 GB SATA Intel Pentium G4400 (3.3 GHz) Fiery FS350 PS: 138 Fonts PCL: 113 Fonts
<b>STORE SPECIFICATIONS</b> <b>Mail Box (Number supported)</b>	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes 30,000 Maximum Pages Stored	<b>Supported Operating Systems</b>	Windows 7 32 and 64 bit / Windows 8.1 32 and 64 bit / Windows 10 32 and 64 bit / Windows Server 2012 64bit only / Windows Server 2012 R2 64bit only / Windows Server 2016 R2 64bit only / MAC OS (10.11, 10.12, 10.13, 10.14) 2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB3.0 x 2 (Rear), USB2.0 x 4 (Rear)
<b>Advanced Space</b>	Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows/7/8.1/10) Concurrent Connections (Max.): SMB: 64, WebDAV: 3 (Active Sessions)	<b>Interface</b>	
<b>Advanced Space available disc space</b>	Approx. 16GB (Standard HDD)	<b>Network protocols</b>	TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port9100, SNT, 802.1X, DHCP, DNS, NTP) PDF1.7, EPS, TIFF6, JDF1.4/JMF(OP) FreeForm v1, v2.1
<b>Advanced Space Features</b>	Approx. 480GB (with option 1TB HDD) Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support Standard: USB Memory	<b>Direct Print</b> <b>VDP</b> <b>Fiery Print Controller Standard Features</b>	Fiery Command WorkStation 6 / Paper Catalog / Fiery Spot-On / Fiery Remote Scan / Fiery Hot Folders & Virtual Printers  Fiery Impose / Fiery Compose / Fiery Impose and Compose / Productivity Package Web Activate (Include Fiery JDF) E400 Debian of Linux
<b>Memory Media</b>		<b>HW Platform</b> <b>Base OS</b> <b>Power source</b> <b>Maximum Power consumption</b> <b>Dimensions (W x D x H)</b> <b>Weight</b>	AC100-240V, 50Hz/60Hz, 3.0A (100V) - 1.3A (240V) 47 W 285 x 93 x 295 mm Fiery unit only (with plate):4.95 kg
<b>SECURITY SPECIFICATIONS</b> <b>Authentication</b>	Standard: Universal Login Manager (Device and Function Level Log-in), uniFLOW Online Express*, User Authentication, Department ID Authentication, Access Management System Optional: My Print Anywhere secure print (Requires uniFLOW) * No charge for this solution; however activation is required.	<b>PAPER SUPPLY OPTIONS</b> <b>PAPER DECK UNIT-E1</b>	Paper Capacity: 3,500 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Thick, Colour, Pre-punched, Letterhead, Bond Paper Size: A4, B5 Paper Weight: 52 to 256 gsm Power Source: From the Main Unit Dimensions (W x D x H): 340 x 630 x 572 mm Weight: Approx. 34 kg
<b>Data</b>	Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated), Common Criteria Certification (DIN ISO 15408) Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, Data Loss Prevention (Requires uniFLOW)	<b>POD DECK LITE-C1</b>	Paper Capacity: 3,500 sheets (80 gsm) Paper Type: Thin, Plain, Recycled, Thick, Colour, Pre-punched, Letterhead, Bond, Tab, Transparency, Label, Coated, Textured, Tracing, Envelope* Paper Size: SRA3, A3, A4, A4R, A5R, B4, B5, B5R, Envelope [No.10(COM10), Monarch, DL, ISO-C5], Custom size: 139.7 x 148.0 mm to 330.2 to 487.7 mm Paper Weight: 52 to 300 gsm Power Source: 220-240V/1.2A 50/60Hz Dimensions (W x D x H): 633 x 686 x 574 mm Weight: Approx. 68 kg *Requires Envelope Feeder Attachment-G1
<b>Network</b>	Standard: IP/Mac Address Filtering, IPSEC, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME	<b>MULTI-DRAWER PAPER DECK-C1</b>	Paper Capacity: 2,000 sheets x 3 drawers, total 6,000 sheets (80 gsm) Paper Type: Thin, Plain, Thick, Recycled, Colour, Pre-punched, Letterhead, Bond, Tab, Transparency, Label, Coated, Textured Paper Size: SRA3, A3, A4, A4R, A5R, B4, B5, B5R, Custom size: 139.7 x 182.0 mm to 330.2 x 487.7 mm Paper Weight: 52 to 300 gsm Power Source: 220-240V/1.7A 50/60Hz Dimensions (W x D x H): 950 x 797 x 1,040 mm Weight: Approx. 155 kg
<b>Document</b>	Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device signature, Secure Watermarks Optional: User signature, Document Scan lock		
<b>ENVIRONMENTAL SPECIFICATIONS</b> <b>Operating Environment</b>	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity)		
<b>Power source</b>	iR-ADV C7565i III/C7570i III: 220-240 V (±10 %), 50/60 Hz (±2 Hz), 10 Amp iR-ADV C7580i III: 220-240 V (±10 %), 50/60 Hz (±2 Hz), 11 Amp CEE 7/7 (230V)		
<b>Plug (Main Unit)</b> <b>Power consumption</b>	Maximum: Approx. iR-ADV C7580i III: 2,500 W, iR-ADV C7570i III/C7565i III: 2,000 W Printing: Approx. 1,472 W*1 Standby: Approx. 136.6 W*1 Sleep mode: Approx. 0.9 W*2 Plugin Off: Approx. 0.3W*3 *1 Reference value: measured one unit *2 0.9W sleep mode is not available in all circumstances due to certain settings. *3 Reference value, Quick start mode OFF		
<b>Noise levels (BW/CL)</b>	<b>Sound Power Level (LwAd)</b> iR-ADV C7580i III: Active(BW): 76.3 dB or Less*1, Active(CL): 75.5 dB or Less*1, Standby: 52 dB*2 iR-ADV C7570i III: Active(BW): 75.5 dB or Less*1, Active(CL): 75.1 dB or Less*1, Standby: 52 dB*2 iR-ADV C7565i III: Active(BW): 75.1 dB or Less*1, Active(CL): 74.7 dB or Less*1, Standby: 52 dB*2 <b>Sound Pressure (LpAm)</b> Bystander's position: (2-sided/1-sided) iR-ADV C7580i III: Active(BW): 55/56 dB*2, Active(CL): 55/56 dB*2, Standby: 34 dB*2 iR-ADV C7570i III: Active(BW): 55/55 dB*2, Active(CL): 54/55 dB*2, Standby: 34 dB*2 iR-ADV C7565i III: Active(BW): 55/55 dB*2, Active(CL): 54/55 dB*2, Standby: 34 dB*2 *1 DE-UZ205 (2017) compliant (*Data taken from Blue Angel Standard value) *2 Reference value: measured only one unit with ISO7779, described with ISO9296 (1988)		
<b>Standards</b>	Blue Angel		



# TECHNICAL SPECIFICATIONS

# imageRUNNER ADVANCE C7500 III series

## OUTPUT OPTIONS COPY TRAY-R2

Provides a simple tray for basic output needs.  
Capacity: 250/100 sheets (1-sided/2-sided, 80 gsm)

## STAPLE FINISHER-V2 (External)

Number of Trays: 3  
Upper Tray Capacity\*: A4, A5, A5R, A6R, B5: 250 sheets, A3, A4R, B4, B5R: 125 sheets  
Mid Tray Capacity\*: A4, A5, A5R, A6R, B5: 250 sheets, A3, A4R, B4, B5R: 125 sheets  
Lower Tray Capacity\*: A4, A5, A5R, B5: 3,000 sheets SRA3, A3, A4R, B4, B5R: 1,500 sheets, A6R: 250 sheets  
\* with 81.4 gsm paper  
Paper Weight: Upper Tray 52 to 256 gsm, Mid Tray 52 to 256 gsm  
Lower Tray 52 to 300 gsm  
Staple Position: Corner, Double  
Staple Capacity: Corner and Double Stapling:  
A4/B5: 65 sheets (52 to 90 gsm)  
A3/A4R/B4: 30 sheets (52 to 90 gsm)  
Eco Staple:  
A3/A4: 5 sheets (52 to 64 gsm)  
4 sheets (65 to 81.4 gsm)  
3 sheets (81.5 to 105 gsm)  
Staple On Demand: 65 sheets (90 gsm)  
Dimensions (W x D x H): 656 x 623 x 1,195 mm (when the extension tray and rotary tray are extended)  
Weight: Approx. 35 kg

## BOOKLET FINISHER-V2 (External)

(Includes the above STAPLE FINISHER-V2 basic staple specifications.)  
Saddle Stitch paper size: A3, A4R, B4, Custom Size (195.0 x 270.0 mm to 304.8 x 457.2 mm)  
Saddle Stitch Staple Capacity: 20 sheets x 10 sets (52 to 81.4 gsm) (including 1 cover sheet up to 256 gsm)  
Non Staple Folded Bunch Capacity: up to 3 sheets (52 to 105 gsm)  
Dimensions (W x D x H): 656 x 623 x 1,195 mm (when the extension tray and rotary tray are extended)  
Weight: Approx. 58 kg

## STAPLE FINISHER-X1 (External)

Number of Trays: 3  
Upper Tray Capacity\*: A4, A5R, B5: 1,500 sheets, SRA3, A3, A4R, A5, B4, B5R, 750 sheets, A6R: 250 sheets  
Mid Tray Capacity\*: A4, A5R, B5: 250 sheets, A3, A4R, A5, A6R, B4, B5R: 125 sheets  
Lower Tray Capacity\*: [Cascade-Load mode] A4, B5 2,500 sheets, [Random-Load mode] A4, B5 2,500 sheets  
\* with 81.4 gsm paper  
Paper Weight: Upper Tray 52 to 300 gsm  
Mid Tray 52 to 300 gsm  
Lower Tray 52 to 300 gsm  
Staple Position: Corner, Double  
Staple Capacity: Corner and Double Stapling:  
A4/B5: 100 sheets (52 to 80 gsm)  
A3/B4/A4R: 50 sheets (52 to 80 gsm)  
Power Source: 100-240V, 50/60Hz, 2.8A  
Dimensions (W x D x H): 782 x 765 x 1,040 mm (when the extension tray is extended)  
Weight: Approx. 64 kg

## BOOKLET FINISHER-X1 (External)

(Includes the above STAPLE FINISHER-X1 basic staple specifications.)  
Saddle Stitch paper size: SRA3, A3, A4R, B4, Custom Size (210.0 x 279.4 mm to 330.2 x 487.7 mm)  
Saddle Stitch Staple Capacity: 20 sheets x 5 sets (60 to 81.4 gsm) (including 1 cover sheet up to 300 gsm)  
Non Staple Folded Bunch Capacity: up to 5 sheets (60 to 105 gsm)  
Power Source: 100-240V, 50/60Hz, 2.8A  
Dimensions (W x D x H): 896 x 765 x 1,040 mm (when the extension tray is extended)  
Weight: Approx. 110 kg

## 2/4 HOLE PUNCHER UNIT-A1

(Requires either the STAPLE FINISHER-V2 or BOOKLET FINISHER-V2)  
Two or Four Holes  
Acceptable Punch Paper Weight: 52 to 300 gsm  
Acceptable Punch Paper Size: Two holes A3, A4, A4R, A5, B4, B5, B5R; Four holes A3, A4  
Power Source: From the Main Unit

## 4 HOLE PUNCHER UNIT-A1

(Requires either the STAPLE FINISHER-V2 or BOOKLET FINISHER-V2)  
Four Holes  
Acceptable Punch Paper Weight: 52 to 300 gsm  
Acceptable Punch Paper Size: Four holes A3, A4, A4R, A5, B4, B5, B5R  
Power Source: From the Main Unit

## PUNCHER UNIT-BG1(2/F4H)

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)  
Two or Four Holes  
Acceptable Punch Paper Weight: 52 to 256 gsm  
Acceptable Punch Paper Size: Two holes A3, A4, A4R, A5, B5R Four holes A3, A4  
Power Source: From the Finisher

## PUNCHER UNIT-BH(S4H)

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)  
Four Holes  
Acceptable Punch Paper Weight: 52 to 256 gsm  
Acceptable Punch Paper Size: Four holes A3, A4, A4R, A5, B4, B5, B5R  
Power Source: From the Finisher

## MULTI FUNCTION PROFESSIONAL PUNCHER-A1 / B1

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)  
Acceptable Punch Paper Size: SRA3, A3, A4, A4R  
Acceptable Punch Paper Weight: Bypass: 52 to 300 gsm; Punch: 75 to 300 gsm  
Supported Punch Dies (Optional) :  
A4: Loose Leaf (2- or 4-hole), Plastic Comb (21-hole), Velo Bind (12-hole), Twin Loop (23- or 34-hole), Color Coil (47-hole)  
Power Source: 230V/50Hz 1.9A  
Dimensions (W x D x H): 445 x 795 x 1,040 mm  
Weight: Approx. 102 kg

## INNER BOOKLET TRIMMER-A1

(Requires the BOOKLET FINISHER-X1)  
Waste Tray Capacity: 1,500 Sheets  
Acceptable Paper Weight: 60 to 300 gsm  
Trim Amount: 2 to 20 mm  
Acceptable Paper Size: 210 x 279.4 mm to 330.2 x 487.7mm  
Power Source: From Finisher

## DOCUMENT INSERTION UNIT-Q1

(Requires either the STAPLE FINISHER-V2 or BOOKLET FINISHER-V2)  
Number of trays: 1  
Tray Capacity: 100 Sheets (80 gsm)  
Acceptable Paper Type: Thin, Plain, Recycled, Colour, Thick, Textured, Bond, Coated, Tab, Letterhead  
Acceptable Paper Sizes: SRA3, A3, A4, A4R, B4, B5, B5R, Acceptable Paper Weight: 60 to 256 gsm  
Power Source: 100-240V/50/60Hz 1.0A  
Dimensions (W x D x H): 247 x 679 x 1,242 mm (width excluding document tray)  
Weight: Approx. 40 kg

## DOCUMENT INSERTION/ FOLDING UNIT-K1

(Requires either the STAPLE FINISHER-V2 or BOOKLET FINISHER-V2)  
Number of trays: 1  
Tray Capacity: 100 Sheets (80 gsm)  
Supported Folding Type: Z-Fold, C-Fold  
Acceptable Paper Type: Z-Fold/C-Fold: Thin, Plain, Recycled, Colour, Insertion Unit: Thin, Plain, Recycled, Colour, Thick, Letterhead, Bond, Coated, Tab, Textured  
Acceptable Paper Sizes: Z-Fold: A3, A4R, B4 C-Fold: A4R  
Insertion Unit: SRA3, A3, A4, A4R, B4, B5, B5R  
Acceptable Paper Weight: Z-Fold/C-Fold: 60 to 105 gsm, Insertion Unit: 60 to 256 gsm  
Power Source: 100-240V/50/60Hz 1.0A  
Dimensions (W x D x H): 247 x 679 x 1,242 mm (width excluding document tray)  
Weight: Approx. 76 kg

## DOCUMENT INSERTION UNIT-N1

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)  
Number of trays: 2  
Tray Capacity: Upper Tray: 200 Sheets (80 gsm), Lower Tray: 200 Sheets (80 gsm)  
Acceptable Paper Type: Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond, Coated, Tab, Tracing, Textured  
Acceptable Paper Sizes: SRA3, A3, A4, A4R, B4, B5, B5R, Custom size (182.0 x 182.0 mm to 330.2 x 487.7 mm)  
Acceptable Paper Weight: 52 to 300 gsm  
Power Source: 100-240V/50/60Hz 1.0A  
Dimensions (W x D x H): 336 x 793 x 1,407 mm (width excluding document tray)  
Weight: Approx. 61 kg

## PAPER FOLDING UNIT-J1

(Requires either the STAPLE FINISHER-X1 or BOOKLET FINISHER-X1)  
Supported Folding Type: Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold  
Acceptable Paper Type: Thin, Plain, Recycled, Colour, Bond  
Acceptable Paper Sizes: Z-Fold: A3, A4R, B4 Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold: A4R  
Acceptable Paper Weight: Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold: 52 to 105 gsm Double Parallel Fold: 52 to 90 gsm  
Power Source: From the Finisher  
Dimensions (W x D x H): 336 x 793 x 1,190 mm  
Weight: Approx. 71 kg

## OTHER OPTIONS STAPLE CARTRIDGE

STAPLE-N1 - for Stapling (3 x 5,000 pcs) (for Staple Finisher-X1 and Booklet Finisher-X1)  
STAPLE-P1 - for Saddle Stitching (2 x 5,000 pcs) (for Booklet Finisher-X1)  
STAPLE CARTRIDGE-X1 - For Stapling (3 x 5,000 pcs) (Staple Finisher-V2 and Booklet Finisher-V2)  
STAPLE CARTRIDGE-Y1 - For saddle stitching (2 x 2,000 pcs) (for Booklet Finisher-V2)

For a complete list of all Hardware accessories, please refer to our website specifications page or online product configurator.

## Software & Solutions



## Certifications and compatibility



Canon Ireland  
3006 Lake Drive  
Citywest, Saggart  
Co. Dublin, Ireland  
Telephone No: 01 2052400  
2052400  
Facsimile No: 01 2052525  
canon.ie

Canon (UK) Ltd  
Woodhatch  
Reigate  
Surrey RH2 8BF  
Telephone No: 01737 220000  
220000  
Facsimile No: 01737 220022  
canon.co.uk

Canon Inc.  
canon.com  
Canon Europe  
canon-europe.com  
English edition  
© Canon Europa N.V., 2019

